

MAKE	PERKINS
MODEL NUMBER	4006-23TAG3A
PRIME POWER	800 kVA
STANDBY POWER	880 kVA
VOLTAGE	230V / 400V
PHASE	THREE PHASE
AMP @ UNITY	925 A
AMP @ 0.8PF	1156 A
ONE STEP LOAD	55% OF AMP RATING

// GENERAL SPECIFICATIONS



ALL CANOPIES ARE WEATHER RESISTANT AND LINED WITH SOUND REDUCTION FOAM
 VENTILATION PARTS ARE DESIGNED WITH MODULAR PRINCIPLES
 CANOPIES ARE ALL METAL AND POWDER-COATED, EQUIPPED WITH LOCKABLE DOORS
 BASE FRAME DESIGN INCORPORATES AN INTEGRAL FUEL TANK
 COASTAL ANTIRUST STAINLESS STEEL OPTIONS ARE AVAILABLE FOR THE CANOPY
 STANDARD FILLER CAP AND FUEL LEVEL GUAGE IS LOCATED INSIDE THE CANOPY
 INCLUDES DIESEL LEVEL SENSOR AND INFORMATION TO THE CONTROLLER
 STANDARD STAINLESS STEEL EXHAUST WITH SILENCER
 PERSONALISED SPECIFICATONS CAN BE ACCOMODATED



	LENGTH	WIDTH	HEIGHT	WEIGHT
STANDARD CANOPY SET DIMENSIONS	6000mm	2200mm	2800mm	11000 kg
SILENT CANOPY SET DIMENSIONS WITH NOSECONE	ON SPECIAL REQUEST ONLY			
FOOTPRINT	6000mm	2200mm		
ADVISED PLINTH SIZE 35MPA REINFORCED	8000mm	4000mm	400mm DEEP	

AVERAGE SOUND WITH STANDARD CANOPY	95 DB AT 7m
AVERAGE SOUND WITH SILENT CANOPY AND NOSECONE	ON SPECIAL REQUEST ONLY
DIESEL TANK SIZE	1000L



// ENGINE SPECIFICATIONS


HEAVY DUTY DIESEL ENGINE

COOLING RADIATOR AND FAN

REPLACEABLE FUEL FILTER, OIL FILTER AND DRY ELEMENT AIR FILTER

FUEL CONNECTION HOSES

DC STARTER AND CHARGE ALTERNATOR



// POWERFUL
GENERATOR
SOLUTIONS

CYLINDER NUMBER	6
CYLINDER ARRANGEMENT	IN LINE
INDUCTION SYSTEM	TURBO CHARGED
BORE	160 mm
STROKE	190 mm
DISPLACEMENT	22.921 L
OIL CAPACITY	113.4 L
OIL TYPE	15W40
COMPRESSION RATIO	13.6:1
GENSET POWER PRIME	640 kW
GENSET POWER STANDBY	704 kW
GOVERNING	ELECTRONIC
FUEL CONSUMPTION 75% LOAD	130 L/H
FUEL CONSUMPTION 100% LOAD	172 L/H

MAKE

MARELLI

OTHER MAKES AND MODELS ARE AVAILABLE

MODEL NUMBER

FLANGE

SAE 1 / 14"

THE ENGINE AND ALTERNATOR ARE CLOSELY COUPLED BY MEANS OF A SAE FLANGE

ANTI-VIBRATION PADS ARE AFFIXED BETWEEN ENGINE ALTERNATOR FEET AND BASE FRAME

BRUSHLESS, SINGLE BEARING SYSTEM

SELF-EXCITING AND SELF-REGULATING

CLOSE VOLTAGE REGULATION

AVR 2/3 PITCH DESIGN AVOIDS EXCESSIVE

NEUTRAL CURRENTS H CLASS INSULATION

STANDARD 2/3 PITCH STARTER WINDINGS



// CONTROL PANEL SPECIFICATIONS

PANEL TYPE

AUTOMATIC MAINS FAILURE PANEL

CONTROLLER TYPE

DEEP SEA 7320



OTHER MAKES AND MODELS ARE AVAILABLE

PANEL AMP RATING	1156 A
ACB AMP RATING AC3	1250 A
CB GENERATOR RATING	
ISOLATOR MAINS	OPTIONAL
EMERGENCY STOP	YES
BATTERY CHARGER	YES
CHANGE OVER INCLUDED	YES



THE CONTROLLER IS A MICROPROCESSOR BASED CONTROL UNIT CONTAINING ALL NECESSARY FUNCTIONS FOR PROTECTION AND CONTROL OF THE GENERATOR UNIT. FURTHERMORE IT CONTAINS A THREE PHASE AC VOLTAGE MEASURING UNIT.

THE CONTROLLER IS EQUIPPED WITH A LCD DISPLAY PRESENTING ALL VALUES AND ALARMS.

THE ALL-IN-ONE CONTROLLER IS DESIGNED FOR THE FOLLOWING APPLICATIONS:

1. AUTOMATIC ENGINE START / STOP
2. ENGINE PROTECTION
3. BREAKER CONTROL
4. GENERATOR PROTECTION



// OPTIONAL SPECIFICATIONS

OPTIONAL

SYNCHRONIZING

FOR KVA REQUIREMENTS LARGER THAN 600 WE SUGGEST YOU CONSIDER SYNCHRONIZATION AS AN OPTION.

- IT IS MORE COST EFFECTIVE FOR THE PURCHASE PRICE, MAINTENANCE AND FUEL CONSUMPTION
- IF UNDERLOAD, GLAZING WILL BE PREVENTED DUE TO THE EFFECTIVE CONTROL ON THE SETS BY REGULATING AND MANAGING THE LOAD REQUIREMENTS AND SWITCHING BETWEEN SETS AUTOMATICALLY
- WHEN BUSY WITH MAINTANCE OTHER SETS CAN STILL PROVIDE POWER



OPTIONAL

CONTROL FUNTIONS

ALL CIRCUITS CAN BE DESIGNED TO MEET SPECIFIED REQUIREMENTS

ALL CONTROLLER MAKES AND MODELS ARE AVAILABLE

GSM MODEMS ARE AVAILABLE FOR SMS AND REMOTE CONTROL

EXTERNAL SIREN AND LIGHT IS AVAILABLE ON REQUEST



OPTIONAL

ISLAND MODE – ONLY AVAILABLE FOR SETS LARGER THAN 150kVA

IN MOST MANUFACTURING SYSTEMS ANY ELECTRICAL SUPPLY INTERRUPTION CAN RESULT IN LARGE MATERIAL AND PRODUCTION LOSSES. THIS NIGHTMARE CAN BE RESOLVED DURING SCHEDULED POWER OUTAGES WITH THE ISLAND MODE. THIS IS A PLC CONTROLLED SYSTEM DESIGNED WITH THE MOST ADVANCED TECHNOLOGY.

